

# Design Document

Crowdsourcing Code Comments with ChatGPT (CrowdDoc)

CSE 4101 Senior Project - Fall 2026

Ahmed Alzahrani and Mohammed Zakry

Faculty Advisor / Client: Professor Marius Silaghi

## 1. Design Overview

CrowdDoc uses a simple web architecture. A user works in a normal browser. The browser talks to a Next.js application server. The server loads the saved C source, parses functions, reads or writes explanations and votes, and can call the Writer and Checker / Reviewer AI.

For Milestone 1, the source is a small Linux v6.12 snapshot with three C files and eleven selected functions. Keeping the source small makes it easier to test the full idea before adding a larger repository.




Figure 1. High-level architecture using the three required areas.

In the current website, the second AI agent appears as Reviewer. This document calls it Checker / Reviewer to match both the project idea and the website label.

## 2. Main Components

**Web Browser / User Interface:** shows folders, files, function source, explanations, forms, and vote controls.

**Application Server:** receives requests, checks input, loads the selected function, starts AI calls, and reads or writes the database.

**Source Browser:** reads the saved Linux v6.12 snapshot and lists known folders/files.

**C Parser:** uses Tree-sitter C to find supported function definitions and basic function information.

**AI Module:** runs the Writer first and then runs the Checker / Reviewer using the saved Writer result.

**Database:** SQLite stores function records, explanations, and votes without changing the Linux source files.

### 3. Module Interfaces / Simple UML

The project uses TypeScript modules and functions instead of large Java-style classes. The UML below is a simple view of the main modules and methods that are already in the project.




Figure 2. Simple UML-style module diagram.

### 4. Module Details

#### 4.1 Source Browser

loadManifest() reads the source manifest. listDirectory() returns the known folders and files. Path checks reject unsafe values such as '..'.

## 4.2 C Parser

parseCFunctions() uses Tree-sitter C to return the function name, source, signature, line range, and content hash.

## 4.3 AI Module

generateWriter() creates the first explanation. generateReviewer() is the Checker / Reviewer step and receives the same function plus the Writer explanation.

## 4.4 Database Module

getFunction() loads one function. listExplanations() loads its comments.

addExplanation() saves AI or human explanations. addVote() saves a vote.

## 4.5 Server Actions

saveExplanation() validates and saves a human correction/addition. castVote() checks the relationship before saving a vote. requestLiveDraft() runs the live Writer and Checker / Reviewer flow.

## 4.6 Web Interface

Next.js pages and React components show the source browser, function page, explanations, human form, breadcrumbs, and voting controls.

## 5. Main User Flow

1. The user opens CrowdDoc.
2. The user browses the saved Linux v6.12 folders and files.
3. The user opens one of the selected C functions.
4. CrowdDoc shows the exact read-only source.
5. The Writer explanation is shown or a live Writer call is requested.
6. The Writer result is saved.
7. The Checker / Reviewer receives the same function and saved Writer result.
8. The Checker / Reviewer / Reviewer result is saved and shown.
9. A user can add a human correction or addition.
10. A user can vote for an explanation.

## 6. User Interface Mock-up

The interface is kept simple. The user first browses the source, then opens a function page, and can add a human correction from that page.




Figure 3. Simple GUI mock-up based on the current website flow.

## 7. Database Design

A Function record represents one exact function version. An Explanation belongs to one Function. A Checker / Reviewer result or human correction can point back to the explanation it answers. A Vote belongs to an explanation.




Figure 4. Simple database relationship diagram.

## 8. Writer and Checker / Reviewer Design

The Writer and Checker / Reviewer are two separate model calls. The Writer receives one C function and creates the first explanation. The Checker / Reviewer receives the same function plus the exact Writer explanation that was saved. This makes the second call a real check of the first result.

If no OpenAI key is configured, prepared Writer and Checker / Reviewer examples can be shown as stand-ins. The page must make that clear. If a live request fails, the user sees a short error message and the API key is not shown.

## 9. Input Validation and Error Handling

- Reject unsafe source paths such as '..'.
- Require text in all four human explanation fields.
- Limit the current human explanation fields to 4000 characters each.
- Only allow a human correction to answer an AI explanation from the same function.
- Only save a vote when the function and explanation match.
- Keep the Writer result if the Checker / Reviewer call fails after the Writer succeeds.

## 10. Communication Between Parts

- Browser to server: normal web requests and Next.js server actions.
- Server to saved source: reads the Linux v6.12 snapshot.
- Server to SQLite: saves and loads functions, explanations, and votes.
- Server to OpenAI: sends the selected function to Writer, then the same function plus saved Writer text to Checker.
- External source link: opens the matching Linux v6.12 file in Elixir/Bootlin.

## 11. Current Limits and Next Work

The current prototype is intentionally small. It has three Linux v6.12 C files and eleven selected functions. It does not yet import a full arbitrary repository. Sign-in is not part of Milestone 1, and reliable user identity, expert verification, and one-vote-per-user protection are planned next-step items after the basic source/comment flow is stable.